



CEB100W SERIES 100 WATT 4:1 INPUT ISOLATED DC-DC CONVERTER

Features

- Efficiency Up to 93.5%
- Fixed Switching Frequency
- Regulated Outputs
- Remote On/Off
- Fully Protected (OTP/OCP/OVP/UVLO)
- 3000Vdc I/O Isolation
- Operating Case Temperature -40 to +105°C
- Eighth Brick Size Meet Industrial Standard
2.45"x1.05"x0.5"
- CB Test Certificate IEC 62368-1
- UL 62368-1 (Basic Insulation) Approval
- Shock & Vibration MIL-STD-810F Compliant
- Fire & Smoke EN 45545-2 Compliant
- 5000m Operating Altitude



MODEL NUMBER	INPUT VOLTAGE	OUTPUT VOLTAGE	OUTPUT CURRENT		INPUT CURRENT		% EFF.		CAPACITOR LOAD MAX.
			MIN.	MAX.	NO LOAD	FULL LOAD	(3)	(2)	
CEB100W-24S05	9-40 VDC	5 VDC	0 mA	20 A	125 mA	4735 mA	92	91	20000uF
CEB100W-24S12	9-40 VDC	12 VDC	0 mA	8.3 A	125 mA	4663 mA	92.5	90.5	8300μF
CEB100W-24S24	9-40 VDC	24 VDC	0 mA	4.2 A	125 mA	4667 mA	90.5	90	4200uF
CEB100W-24S48	9-40 VDC	48 VDC	0 mA	2.1 A	125 mA	4625 mA	90.5	90.5	1000uF
CEB100W-24S54	9-40 VDC	54 VDC	0 mA	1.85 A	125 mA	4574 mA	91	91	1000uF
CEB100W-48S05	16.5-74 VDC	5 VDC	0 mA	20 A	80 mA	2252 mA	93.5	92.5	20000uF
CEB100W-48S12	16.5-74 VDC	12 VDC	0 mA	8.3 A	80 mA	2255 mA	93	92	8300μF
CEB100W-48S24	16.5-74 VDC	24 VDC	0 mA	4.2 A	80 mA	2320 mA	91	90.5	4200uF
CEB100W-48S48	16.5-74 VDC	48 VDC	0 mA	2.1 A	80 mA	2308 mA	91	91	1000uF
CEB100W-48S54	16.5-74 VDC	54 VDC	0 mA	1.85 A	80 mA	2287 mA	91.5	91	1000uF

NOTE:

1. Nominal input voltage 24, 48V_{dc}.
2. Measured at nominal input voltage.
3. Measured at 12V_{dc} for 24V_{in}, 24V_{dc} for 48V_{in}.

PART NUMBER

Series	Nominal Input Voltage	Number of Outputs	Nominal Output Voltage	Remote On/Off Logic	Mounting Inserts	Operating Case Temp. Range
CEB100W-	II	O	XX	L	-Y (Option)	-Z (Option)
CEB100W	24 : 24 VDC 48 : 48 VDC	S : Single	05 : 5.0VDC 12 : 12VDC 24 : 24 VDC 48 : 48VDC 54 : 54VDC	None : Positive N : Negative	-F : Flanged Baseplate with M2.5 mounting insert	None : -40~105°C

Part Number Example:

CEB100W-48S12N: Eighth Brick, 100W, 4:1 16.5-74Vdc Input, Single 12Vdc Output, Negative Logic, -40~105°C Operating Case Temp. Range



CEB100W Series

TECHNICAL SPECIFICATIONS

(All specifications are typical at nominal input, full load at 25°C unless otherwise noted.)

ABSOLUTE MAXIMUM RATINGS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Input Voltage	Continuous	24Vin 48Vin	-0.3 -0.3		40 75	V _{dc}
Input Surge Voltage	100ms max.	24Vin 48Vin			50 100	V _{dc}
Operating Ambient Temperature	At the center part of case plate (with derating)	All	-40		105	°C
Maximum Case Temperature		All			110	°C
Storage Temperature		All	-55		125	°C

INPUT CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Operating Input Voltage		24Vin 48Vin	9 16.5	24 48	40 75	V _{dc}
Input Under Voltage Lockout						
Turn-On Voltage Threshold		24Vin 48Vin	8 15.7	8.5 16	8.8 16.3	V _{dc}
Turn-Off Voltage Threshold		24Vin 48Vin	7.7 14.7	8 15	8.3 15.3	V _{dc}
Lockout Hysteresis Voltage		24Vin 48Vin		0.6 1		V _{dc}
Maximum Input Current	V _{in} =9V, Full load. V _{in} =16.5V, Full load	24Vin 48Vin		13.5 6.8		A
No-Load Input Current	V _{in} =24, 48V, I _o =0A	See Model Number Table				mA
Input Filter	Pi filter	All				
Inrush Current (I ² t)	As per ETS300 132-2	All			0.1	A ² s
Input Reflected Ripple Current	P-P thru 12uH inductor, 5Hz to 20MHz	All		30		mA

OUTPUT CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Voltage Set Point Accuracy	V _{in} =24, 48V, Full load, T _c =25°C	All	-1.0		+1.0	%
Output Voltage Regulation						
Load Regulation	Full load to no load	All			±0.2	%
Line Regulation	V _{in} =High line to low line, full load	All			±0.2	%
Temperature Coefficient	T _c =-40°C to 105°C	All			±0.02	%/°C
Output Voltage Ripple and Noise (5Hz to 20MHz bandwidth)						
Peak-to-Peak	Full load, 10uF polymer and 1.0uF ceramic capacitors	5Vo 12Vo 24Vo 48Vo 54Vo			100 150 240 480 480	mV
RMS		5Vo 12Vo 24Vo 48Vo 54Vo			40 60 100 200 200	



CEB100W Series

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Output Current Range	V _{in} = 9 to 36V, 18 to 75V	See Model Number Table				A
Over Current Protection	Hiccup mode. Auto recovery	All	110	125	160	%
Over Voltage Protection	Limited voltage	5Vo	112		130	%
		12Vo	122		135	
		24Vo	122		135	
		48Vo	112		130	
		54Vo	106		115	
Short Circuit Protection		All	Continuous, Auto Recovery			
External Load Capacitance	Full load (resistive)	See Model Number Table				uF
Output Voltage Trim Range	P _o ≤ max. rated power, I _o ≤ I _{o_max} .	5Vo	-20		+10	%
		12Vo	-20		+20	
		24Vo	-20		+20	
		48Vo	-20		+10	
		54Vo	-20		+5	

EFFICIENCY

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
100% Load	$V_{in} = 24V$, $48V$	See Model Number Table				%

DYNAMIC CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Output Voltage Current Transient						
Error Band	75% to 100% of I_{o_max} step load change $dI/dt = 0.1A/\mu s$ (within 1% V_{out} nominal)	All			± 5	%
Recovery Time		All			250	μs
Turn-On Delay and Rise Time	Full load (constant resistive load)					
Turn-On Delay Time, From On/Off Control	$V_{on/off}$ to 10% V_{o_set} , Remote on	All		30		ms
Turn-On Delay Time, From Input	V_{in_min} to 10% V_{o_set} , Power up	All		30		ms
Output Voltage Rise Time	10% V_{o_set} to 90% V_{o_set}	All		30		ms

ISOLATION CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Isolation Voltage (100% factory Hi-Pot tested @2sec.)	1 Minute; input to output	All			3000	V_{dc}
	1 Minute; input to case				1600	
	1 Minute; output to case				1600	
Isolation Resistance	Input to output	All	1			$G\Omega$
Isolation Capacitance	Input to output	All		1000		pF
	Input to case			NC		
	Output to case			NC		

FEATURE CHARACTERISTICS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Switching Frequency	Pulse width modulation (PWM), fixed	All	270	300	330	KHz
On/Off Control, Positive Remote On/Off Logic, Refer to -Vin Pin						
Logic Low (Module Off)	$V_{on/off}$ at $I_{on/off} = 1.0mA$	All	0		1.2	V
Logic High (Module On)	$V_{on/off}$ at $I_{on/off} = 0.0\mu A$, Pin open=On	All	3.5		75	V
On/Off Control, Negative Remote On/Off Logic, Refer to -Vin Pin						
Logic High (Module Off)	$V_{on/off}$ at $I_{on/off} = 0.0\mu A$, Pin open=Off	All	3.5		75	V
Logic Low (Module On)	$V_{on/off}$ at $I_{on/off} = 1.0mA$	All	0		1.2	V
On/Off Current (for Both Remote On/Off Logic)	$I_{on/off}$ at $V_{on/off} = 0V$	All		0.3	1	mA
Leakage Current (for Both Remote On/Off Logic)	Logic high, $V_{on/off} = 15V$	All			30	μA



CEB100W Series

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
Off Converter Input Current	Shutdown input idle current	All		5	10	mA
Over Temperature Shutdown	Temperature at the center part of case, non-latching	All		110		°C
Over Temperature Recovery		All		100		°C

GENERAL SPECIFICATIONS

PARAMETER	NOTES and CONDITIONS	Device	Min.	Typ.	Max.	Units
MTBF	$I_o = 100\%$ of $I_{o_max.}$; MIL-HDBK - 217F_Notice 1, GB, 25°C	05Vo		1000		K hours
		12Vo				
		24Vo		980		
		48Vo 54Vo				
Weight		All		49		grams
Case Material	Plastic, DAP, UL 94V-0					
Base plate Material	FR4					
Potting Material	UL 94V-0					
Pin Material	Base: Copper Plating: Nickel with Matte Tin					
Shock/Vibration	MIL-STD-810F Compliant					
Humidity	95% RH max. Non condensing					
Altitude	5000m Operating altitude, 12000m Transport altitude					
Thermal Shock	MIL-STD-810F					
Fire & Smoke	EN 45545-2 Compliant					

EMC SPECIFICATIONS (External components required, please refer to application note.)

EMI	Meets EN 55032, External Input Filter		Class A & B
ESD	EN 61000-4-2	Level 3: Air ±8kV, Contact ±6kV, external components required	Perf. Criteria A
Radiated Immunity	EN 61000-4-3	Level 3: 80~1000MHz, 20V/m, external components required	Perf. Criteria A
Fast Transient	EN 61000-4-4	Level 3: On power input port, ±2kV, external components required	Perf. Criteria A
Surge	EN 61000-4-5	Level 4: Line to earth, ±4kV, Line to line, ±2kV, external components required	Perf. Criteria A
Conducted Immunity	EN 61000-4-6	Level 3: 0.15~80MHz, 10V	Perf. Criteria A
Application Note Link			CEB100W Series App Notes
Packaging Information Link			Packaging Information



CEB100W Series

Immunity to Environmental Conditions.

Phenomenon	Reference Clause	Reference Standard	Test Conditions	Result
Vibration Test	MIL-STD-810F Table 514.5C-VIII Figure 514.5C-6	MIL-STD-810F	Unit are Non-Operating Vibration Waveform: Random Vibration Frequency: 15 ~ 2000Hz Total Grms: 4.02621 grms Vibration axis: X、Y、Z axis Test time: 1 hour (each axis) Total Test Time: 3 hour	Pass
Shock Test	MIL-STD-810F 516.5 Table 516.5-I	MIL-STD-810F	Wave Form: Half sine wave Test Category: Crash Hazard Test for Ground Equipment Peak Acceleration: 75G Duration: 10 ms Cross-Over Frequency: 80Hz No. of Shock: Each axis 3 times Shock Direction: $\pm X$, $\pm Y$, $\pm Z$ axis	Pass
Thermal Shock Cycling Test	MIL-STD-810F 503.4 Figure 503.4-1	MIL-STD-810F	Number of shocks: 240 Temperature change: -55°C/+125°C Transfer time: 1min. Max Steady State Time: 30 min. Status of Unit: unit not operating	Pass
Thermal Humidity Cycling Test	MIL-STD-810F Notice 3 Method 507.4	MIL-STD-810F	Number of Cycles: 10Cycle, total 240Hrs Relative Humidity Variation: 95%RH Temperature Variation: 30°C to 60°C Status of Unit: unit not operating	Pass

EN 45545-2 Fire & Smoke Test Conditions.

Item		Standard	Hazard Level
R22	Oxygen Index Test	EN 45545-2: 2013+A1:2015 EN ISO 4589-2: 2017	HL1, HL2, HL3
	Smoke Density Test	EN 45545-2: 2013+A1:2015 EN ISO 5659-2: 2017	HL1, HL2, HL3
	Smoke Toxicity Test	EN 45545-2: 2013+A1:2015 NF X70-100-1&2: 2006	HL1, HL2, HL3
R23	Oxygen Index Test	EN 45545-2: 2013+A1:2015 EN ISO 4589-2: 2017	HL1, HL2, HL3
	Smoke Density Test	EN 45545-2: 2013+A1:2015 EN ISO 5659-2: 2017	HL1, HL2, HL3
	Smoke Toxicity Test	EN 45545-2: 2013+A1:2015 NF X70-100-1&2: 2006	HL1, HL2, HL3
R24	Oxygen Index Test	EN 45545-2: 2013 EN ISO 4589-2	HL1, HL2, HL3
R25	Glow - Wire Test	EN 45545-2: 2020+A1:2023 EN 60695-2-11:2014	HL1, HL2, HL3
R26	Vertical Flame Test	EN 45545-2: 2013+A1:2015 EN 60695-11-10: 2013	HL1, HL2, HL3




CEB100W Series


CHARACTERISTIC CURVE

Power Derating Curve


CEB100W-24S05, 54 Derating Curve
without Heatsink ($V_{in}=24V$)




CEB100W-24S05, 54 Derating Curve
with Heatsink ($V_{in}=24V$)




CEB100W-24S12, 48 Derating Curve
without Heatsink ($V_{in}=24V$)




CEB100W-24S12, 48 Derating Curve
with Heatsink ($V_{in}=24V$)



CEB100W-24S24 Derating Curve
without Heatsink ($V_{in}=24V$)











CEB100W-24S24 Derating Curve
with Heatsink ($V_{in}=24V$)













CEB100W Series













Performance Data

CEB100W Series









CEB100W Series






CEB100W Series





CEB100W Series

MECHANICAL SPECIFICATION



All Dimensions in Inches[mm]

Tolerance Inches: x.xx=±0.02, x.xxx=±0.010

Millimeters: x.x=±0.5, x.xx=±0.25


Pin Connection

Pin	Function
1	+V Input
2	On/Off
3	-V Input
4	-V Output
5	-Sense
6	Trim
7	+Sense
8	+V Output

Note: Pin Size is $\phi 0.04 \pm 0.004$ Inch [$\phi 1.0 \pm 0.1$ mm]

Pin Size is $\phi 0.06 \pm 0.004$ Inch [$\phi 1.5 \pm 0.1$ mm]

-F: Flanged Baseplate



All Dimensions in Inches[mm]

Tolerance Inches: x.xx=±0.02, x.xxx=±0.010

Millimeters: x.x=±0.5, x.xx=±0.25

Pin Connection

Pin	Function
1	+V Input
2	On/Off
3	-V Input
4	-V Output
5	-Sense
6	Trim
7	+Sense
8	+V Output

Note: Pin Size is $\phi 0.04 \pm 0.004$ Inch [$\phi 1.0 \pm 0.1$ mm]

Pin Size is $\phi 0.06 \pm 0.004$ Inch [$\phi 1.5 \pm 0.1$ mm]

CINCON Electronics Co. Ltd.

Add: 14F, No. 306, Sec.4, Hsin Yi Rd., Taipei, Taiwan

Tel: 886-2-27086210

Fax: 886-2-27029852

E-mail: sales@cincon.com

Web: www.cincon.com